



SOR Belgium

Klaverbladstraat 21,
3560 Lummen

Tel. + (32) 13 45 80 40

advies@sorbelgium.be
www.sorbelgium.be

SOR BOX

FOR URBAN DISTRIBUTION AND LOGISTICS

TECHNICAL SHEET

Palletized transport

MODEL SP33

| Description | Thickness |
|-------------|---------------------|
| Floor | 125mm |
| Bulkhead | 90mm |
| Rear doors | 90mm |
| Sidewalls | 90mm |
| Roof | 110mm |
| Locks | 4 st st with handle |
| Hinges | 6/8 st st |

ATP/IR/FRC
12000<GRW ≤ 26000Kg (N3)

| Dimensions | Internal/External |
|------------|-----------------------------|
| Length | 4100/10000mm |
| Width | 2300/2590mm |
| Height | 2300/3100mm (ESP)-3265mm |



Box standard equipment

Composition

- GRP floor (glass fiber reinforced plastic) finished in grey colour
- High resistance 3mm st st rear frame
- Four horizontal rear bumpers for docks protection
- Five lips gummi protection on doors
- St st door retainers
- 250x60mm aluminun quickstrip surface mounted
- W gummi protection on doors
- GRP external cappings
- St st subframe
- One internal light recessed mounted for <6000mm length with switch placed in cabin
- Two internal lights recessed mounted for length ≥6000mm
- Thermoplastic mudguards with gummi mudflaps
- Retractable rear Ladder
- Galibo lights according to EC regulation



SOR IBÉRICA SA, in its continual efforts to meet the needs of its customers, remarks that each and every one of its products are open to be changed or improved. These modifications may or may not appear on the website or any of the communication tools that the company uses. This will often depend whether the site or any other communication tool has been brought up to date or not. Thereof, it is advisable to confirm the conditions of these before placing an order.

Optional equipment

Accessories

TIR finition
 Working light
 Tool box or extinguisher
 Lames curtain
 Tail lift installation
 Cooling engine installation
 Fixed partition wall
 Sliding bulkhead
 Multi storage panels
 Any colour box
 Side lights
 Security lock
 Ventilation window
 Retractable side guard
 EC approvals
 ATP or Type approval
 Reinforcements for logistics
 Customer levelling

Sidewalls

Recessed aluminum quickstrip
 St st quickstrip
 Stainless steel, aluminum or GRP
 sidewalls protection
 Load restraint rails
 Double decks recessed rails
 Side door

Rear doors

St st door protections

Floor

Aluminum floor partial or complete
 st st rear frame prolongation
 Grooved floor
 St st floor plate
 Drain pipes
 Wheels bypass
 Recessed or Surface mounted rails
 Rear channel for waste water

Roof

LED extra internal lights
 Reinforcements for sliding
 bulkhead
 Recessed lames curtain
 Rear evaporator installation
 Load restraint rails

